## Engineered LarchFlooring





## **DECLARATION OF PERFORMANCE: RWINTENGLGE001**

Product type identification	RWINTENGLGE001
Product description	Engineered Larch Flooring
Intended use	Engineered wood flooring, for use in accordance with EN13489.
Manufacturer information	Russwood Ltd Station Sawmill Newtonmore PH20 1AR Scotland www.russwood.co.uk mail@russwood.co.uk/01540 673648
AVCP System	AVCP 4
In case of the DoP concerning a construction product covered by a harmonised standard:	The manufacturer has taken responsibility for initial type testing and implementation of FPC, in accordance with AVCP level 3.
Harmonised technical specification – BS EN 13489:2017, and EN14342 - 2013	
Essential characteristics	Performance
Density:	530kg/m3
Reaction to fire:	Cfl-S1 when used under the conditions for CWFT set out in EN14342 – 2013
Durability without treatment:	Class 3
Formaldehyde class:	< Class E1 (<0.124mg/m³)
Content of pentachlorophenol	< 5 ppm
Water vapour permeability:	NPD
Release of other dangerous substances:	NPD
Sound absorption coefficient:	NPD
Thermal conductivity:	NPD
The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of conformity is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above. Signed for and on behalf of the manufacturer by:	John Russell Managing Director Newtonmore 31/01/2024

www.russwood.co.uk





